



INSTALLATION INSTRUCTIONS

300 W. Pontiac Way Clovis, CA 93612 toll free: 1-800-445-3767 web: www.belltech.com

ALIGNMENT INSTRUCTIONS 2004 FORD F-150 REGULAR CAB, SUPER CAB, SUPER CREW

Thank you for being selective enough to choose our high quality BELLTECH PRODUCT. We have spent many hours developing our line of products so that you will receive maximum performance with minimum difficulty during installation.

- Note: Confirm that all of the hardware listed in the parts list is in the kit. **DO NOT** begin installation if any part is missing. Read the instructions thoroughly before beginning this installation.
- Warning:** **Do not** work under a vehicle supported by only a jack. Place support stands securely under the vehicle in the manufacturer's specified locations unless otherwise instructed.
- Warning:** **Do not** drive vehicle until all work has been completed and checked. Torque all hardware to values specified.
- Reminder: Proper use of safety equipment and eye/face/hand protection is absolutely necessary when using these tools to perform procedures!
- Note: It is very helpful to have an assistant available during installation.

RECOMMENDED TOOLS:

- Properly rated floor jack and six & support stands
- Wheel chocks
- Metric socket set
- Metric box wrench set
- Pneumatic die grinder with carbide metal cutting bit
- Pneumatic 1/2" drive impact wrench
- Scribe
- Safety Glasses

IMPORTANT NOTE:

! This process is not normally needed for the Belltech 2" coils but is recommended for use with the Belltech 3" drop coil springs allowing for additional adjustment to obtain proper alignment.

LENGTHENING THE ALIGNMENT SLOT

1. Remove the bolts from the lower control arm using a 21mm & 27mm wrench and or socket.
2. Pull the lower control arms down and out of the way to allow for a working area within the slotted holes (photo 1).
3. Insert a stock bolt in the slot locations on the lower control arm mount, position the bolt against inner slot side then scribe a line along the bolt flange (Photo 2). It is helpful to outline the profile so it can be easily followed while cutting (Photo 3). Perform this marking technique on all eight slots.
4. Using a die grinder and carbide metal cutting bit remove the material outlined as preformed in step 3 (Photo 4). Photo 5 shows proper material removal.

5. Once all the holes have been slotted remove any burrs then reattach the lower control arms.

